



Specifications Philips LED Panel  
 FlexBlend RC340B White 30W 4200lm -  
 940 Cool White | 120x30cm - UGR <19  
 - Best Colour Rendering - Motion and  
 Light Sensor

[View Product](#)

## General Information

|                          |  |
|--------------------------|--|
| SKU                      | 243180                                   |
| EAN                      | 8719514708310                            |
| Brand                    | Philips                                  |
| Manufacturer Name        | RC340B LED42S/940 SRD W30L120 VPC PCS U4 |
| Any Lamp all-in warranty | 5 Years                                  |
| Average Lifetime (h)     | 50000                                    |
| Series                   | RC340B                                   |

## Technical Information

|                             |                    |
|-----------------------------|--------------------|
| Technology                  | LED Integrated     |
| Voltage (V)                 | 220-240            |
| Dimmable                    | Dimmable with Dali |
| Colour Code                 | 940 Cool White     |
| Colour temperature (Kelvin) | 4000 Cool White    |
| Colour Rendering (Ra)       | 90-99              |
| Colour of Light             | White              |
| Light colour options        | Single Color       |
| Luminous Efficacy (lm/W)    | 140                |
| IP-rating                   | IP54               |
| Impact Protection (IK)      | IK02 - 0.20 joule  |

|                    |                               |
|--------------------|-------------------------------|
| Fixture Connection | PI [Push-in connector 3-pole] |
|--------------------|-------------------------------|

|              |       |
|--------------|-------|
| Power factor | >0.90 |
|--------------|-------|

|                       |           |
|-----------------------|-----------|
| Product Type Category | LED Panel |
|-----------------------|-----------|

## Fixture Information

|      |          |
|------|----------|
| EOC8 | 70831000 |
|------|----------|

|                 |          |
|-----------------|----------|
| Mounting Method | Recessed |
|-----------------|----------|

|                      |                                |
|----------------------|--------------------------------|
| Unified Glare Rating | < 19 - for offices and schools |
|----------------------|--------------------------------|

|               |                    |
|---------------|--------------------|
| Optical Cover | PC (Polycarbonate) |
|---------------|--------------------|

|                       |            |
|-----------------------|------------|
| Operating Temperature | +10 to +40 |
|-----------------------|------------|

|                    |                   |
|--------------------|-------------------|
| Emergency Lighting | No Emergency Unit |
|--------------------|-------------------|

|                       |       |
|-----------------------|-------|
| Colour of the Fixture | White |
|-----------------------|-------|

|         |       |
|---------|-------|
| Housing | Steel |
|---------|-------|

|                    |       |
|--------------------|-------|
| Colour of material | White |
|--------------------|-------|

## Dimensions

|                |          |
|----------------|----------|
| LED panel size | 120x30cm |
|----------------|----------|

|             |      |
|-------------|------|
| Length (mm) | 1197 |
|-------------|------|

|            |     |
|------------|-----|
| Width (mm) | 297 |
|------------|-----|

|             |    |
|-------------|----|
| Height (mm) | 60 |
|-------------|----|

## Sensor Information

|                |
|----------------|
| Type of sensor |
|----------------|

**Why Any-lamp?**  
Light Sensor

 Order from the **largest lighting specialist** in Europe  **Customised** quotation

 Up to **7 years warranty**  **Easy** return process